




**Astro-
und Feinwerktechnik
Adlershof GmbH**

Albert-Einstein-Str.12
D-12489 Berlin

Phone: +49- 30- 6392 1000
Fax: +49- 30- 6392 1002
Internet: www.astrofein.com

Space Technology

AOCS-Components



Reaction Wheel RW 1 for Pico and Nano Satellites

The RW 1 is a **flight proven** high integrated Reaction Wheel with the following features:

- Separate wheel drive electronics (WDE) for up to four Reaction Wheels
- PI controller for speed and acceleration
- Two different rotating masses available (Type A or Type B)
- Four different standard data interfaces available
- Low level emitted vibrations, due to the mechanical design and the high level of alignments and balancing

Parameter**Data**

	Type A	Type B
Performance:		
Angular momentum (@ 8 000 rpm)	$5.8 \cdot 10^{-4}$ Nms	$1.0 \cdot 10^{-4}$ Nms
Nominal rotation speed	8 000 rpm	
Max. rotation speed	approx. 16 000 rpm	
Nominal torque	$23 \cdot 10^{-6}$ Nm	$4 \cdot 10^{-6}$ Nm
Mechanical:		
Mass		
wheel	≤ 20 g	≤ 12 g
WDE	≤ 45 g	
Dimension		
wheel with flange	21 mm x 21 mm x 12 mm	
WDE	95 mm x 50 mm x 15 mm	
Moment of inertia (rotating mass)	$7.0 \cdot 10^{-7}$ kgm ²	$1.2 \cdot 10^{-7}$ kgm ²
Electrical:		
Voltage	5 V	
Power consumption		
Standby (WDE only)	≤ 0.40 W	
Nominal speed (WDE + single wheel)	≤ 0.62 W	
Maximum (WDE + single wheel)	≤ 0.72 W	
Data Interfaces:	CAN2.0, RS232, RS485, SPI (others on request)	
General:		
Operation temperature range	-20°C to +50°C	
Non-operation temperature range	-30°C to +60°C	
Design lifetime	1 year in low earth orbit	
Storage time	1 year (incl. up to 240 h of ground operation)	

All rights are reserved. Subject to change without prior notice.